


NEF 67

550EVO Rated at 550 Mhp @ 3200



SPECIFICATIONS

Type	Diesel 4 Stroke Inline 6
Configuration	Cylinder Turbocharged
Air Handling	Air Cooled 104 x 132
Bore X stroke	mm 6.7 L 15.9 : 1 4 CCW
Displacement	Electronic Common
Compression Ratio	Rail CGI Heat Treated
Valves per Cylinder	Steel
Rotation	Aluminum Double Lip
Fuel System	Re-entrant
Cylinder Head Material	.750 kg/m2
Over Head Camshaft	72-80C
Piston	Yes
	HXC
Moment of Inertia	
Temperature Regulation	
Cold Start Aid	
Cooling System	


RATINGS

550 Mhp @ 3200	1184 ft/lbs @ 1750 RPM
----------------	------------------------

STANDARD CONFIGURATION

Emissions Level	EPA Tier 3
Flywheel SAE1	11"
Flywheel Housing	Aluminum
Flywheel Housing	SAE 3
Oil Sump	Aluminum 10 Degree Static
Voltage	12 and 24v
Alternator	70A and 90A
Starter	3 kW
Dimensions LxWxH	42.8" x 33.3" x 32.4"
Weight Dry	1610 lbs
Weight Wet	1670 lbs

FPT N67 550 EVO Performance



N67 550 Mhp — RATING A1 - 404 kW

Engine Speed (r p m)	Peak Power (Mhp)	Propeller Power (Mhp)	Torque (ft/ lbs)	Propeller Fuel Consumption (gal/ hr)	Consumption (g/kWh)
600	44.9	1.6	393	0.1	255
800	66.6	4.2	437	0.2	240
1000	88.4	8.6	464	0.5	233
1200	125.1	17.6	548	0.9	228
1400	202.6	38.8	760	2.0	226
1600	333.2	83.3	1094	4.1	213
1800	405.3	128.2	1183	6.2	209
2000	444.7	173.7	1168	8.4	211
2200	469.2	221.8	1120	10.8	212
2400	495.0	278.5	1083	13.9	217
2600	516.8	341.2	1044	17.4	221
2800	535.8	410.3	1005	21.0	222
3000	549.4	482.9	962	24.7	222
3200	549.4	549.4	902	28.4	225

= Range of highest engine efficiency

NEWFOUNDLAND & LABRADOR

141 Glencoe Drive
Mount Pearl, NL | A1N 4S7
Phone: (709) 726-6774
Email: sales@madsenpower.ca

ONTARIO

30 Voyager Court South
Toronto, Ontario | M9W 5M7
Phone: (416) 907-3844
Email: sales@madsenpower.ca

